



VARDAflex Eco Reach20 M-Rolle Flex.LEDStrip, 24V, Innen, 3000K

Article nr.: 82205-V2

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 100 mm or 6 LEDs · Number of LEDs: 1.200 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · Lumen per meter: 411 lm · Voltage: 24V DC · Power per meter: 5 W · Lifetime L70B50: >= 50.000 h · energy efficiency class: G · LxWxH in mm: 20.000 x 10 x 1,6 · · Easy installation with solderless connector (optional). · Maximum length per connection: 20 meter. New connectors for greater length. · Delivery contents: 20 meter reel with connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094812052
Housing colour	Weiss
Length	20000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	8220.00 lm
Lightoutput per LED	6.85 lm
Lamp	Inklusive LED





VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K
Article nr.: 82205-V2

TECHNICAL DATA

IP rating	20
Power	100 W
Current mA	4.200 mA
Voltage	24 V
Amount of LED	1200
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	50.000 h





VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K
Article nr.: 82205-V2

TECHNICAL DRAWING

