



VARDAflex Eco Reach20 M-Rolle Flex.LEDStrip, 24V, Innen, 4000K

Article nr.: 82208

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 1200 · LED pitch: 16,67 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · Lumen per meter: 428 lm · Voltage: 24V DC · Power per meter: 5 W · Lifetime L70: >= 50,000 h · energy efficiency class: G · LxWxH in mm: 20,000 x 10 x 1.6 · Easy installation with solderless connector (optional). · Maximum length per connection: 20 meter. New connectors for greater length. · Delivery contents: 20 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094822082
Housing colour	Weiss
Length	20000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	8560.00 lm
Lightoutput per LED	7.13 lm
Lamp	Inklusive LED





VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82208

TECHNICAL DATA

IP rating	20
Power	100 W
Psb	0,00 W
Current mA	4.200 mA
Voltage	24 V
Amount of LED	1200
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	50.000 h





VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82208

TECHNICAL DRAWING

