




VARDAflex Eco Standard Reach30 M-R. Flex.LEDStrip, 24V, Innen, 4000K

Article nr.: 82318

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 1800 · LED pitch: 16,67 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · Lumen per meter: 247lm · Voltage: 24V DC · Power per meter: 3 W · Lifetime L70B50: >= 36,000 h · energy efficiency class: G · LxWxH in mm: 30,000 x 10 x 1.5 · Easy installation with solderless connector (optional). · Maximum length per connection: 30 meter. New connectors for greater length. · Delivery contents: 30 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094823188
Housing colour	Weiss
Length	30000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	7410.00 lm
Lightoutput per LED	4.11 lm
Lamp	Inklusive LED






VARDAflex Eco Standard Reach30 M-R.
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82318

TECHNICAL DATA

IP rating	20
Power	90 W
Current mA	3.750 mA
Voltage	24 V
Amount of LED	1800
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	36.000 h





VARDAflex Eco Standard Reach30 M-R.
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82318

TECHNICAL DRAWING

