

U∩RD∩FL€X Mini Ultra

The **VARDAFLEX** LED strip is only suitable for installation in dry indoor rooms.



Risk of electric shock!

Be sure to have a professional electrician complete installation. There is no warranty coverage for any lights installed without observing european safety directives.



Caution!

Only connect the VARDAFLEX LED strip to a suitable power supply (24 V DC).

Only operate when completely unrolled. Connect VARDAFLEX LED strips in parallel.

Delivery includes

1 x 5 metre **V∕IRD⁄IFL€X** LED strip

Technical data

Power supply 24 V power supply with constant

output voltage

75 W Power Current strength 3.125 A Radiation angle 120° Quantity LED 350

Length maximum 5 metres per connection

Dimensions 5000 x 5 x 1,5 mm

Bending diameter 60 mm



Compliant with the applicable


european CE directives







Very light - profile necessary The **VARDAFLEX** LED strip needs an additional cooling element and





Suitable for indoor use only

Installation



Risk of electric shock!

Switch off voltage prior to installation. Ensure that voltage cannot be accidentally switched on again.



!\ Caution!

On conducting surfaces, place an insulation layer between the **VARDAFLEX** LED strip and surface. Surfaces must be flat, free of dust, grease and dry.

- 1. Prepare surface.
- 2. Shorten **VARDAFLEX** LED strip if necessary (Fig. 1).
- 3. Peel off adhesive film and gently press on VARDAFLEX LED strip, do not press directly on the LEDs.
- 4. Connect VARDAFLEX LED strip to power supply.


Shortening the LED strip



Risk of electric shock!

Always disconnect the mains plug before shortening.

VARDAFLEX LED strip can be separated in each case after seven LEDs (100 mm) (Fig. 1).



Separate the **VARDAFLEX** LED strip at the marked position. For a tightly assembled LED strip is a micro side cutter or an optional cutter required.



∠!\ Caution!

With soldered connections note that the soldering temperature is 260° C and the soldering duration a maximum of 10 seconds per soldering point.

Only use neutral cross-linked silicon (never use silicon which includes vinegar!).

Disposal

Dispose of electrical and electronic equipment in an environmentally friendly manner. Please contact your local council for further information.



