


VARDAflex COB Plus Profi Select 2700-6500K Flex. LED-Strip, IP20, TW 2700-6500K, COB


Article nr.: 74369

flexible LED Strip with self adhesive backside · for indoor use, IP20 · · can be seperated every 62.5 mm or 32 LEDs · number of LEDs: 2560 · LED pitch: 1.95 mm · beam angle: 130° · CRI: >90 · luminous flux per meter: 1500 lm · voltage: 24 V DC · power per meter: 15 W · lifespan L70B50: >= 36,000 h · energy efficiency class: F · LxWxH in mm: 5,000 x 10 x 2.9 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 metre. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094743691
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	2.90 mm
LED colour	2700-6500K tunable white
Lightoutput per fixture	7500.00 lm
Lightoutput per LED	2.93 lm
Lamp	including LED







VARDAflex COB Plus Profi Select 2700-6500K Flex. LED-Strip, IP20, TW 2700-6500K, COB

Article nr.: 74369

TECHNICAL DATA

IP rating	20
Power	75 W
Psb	0,00 W
Current mA	3125 mA
Voltage	24 V
Amount of LED	2560
Temperature range	-20 - 40
LED per meter	512
Dimension of segments	62.50 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	36.000 h
Lifetime L90B10	20.000 h
Suitable light source	





VARDAflex COB Plus Profi Select 2700-6500K Flex. LED-Strip, IP20, TW 2700-6500K, COB
Article nr.: 74369

TECHNICAL DRAWING

