**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# VARDAflex Plus DTW 5 M- R. Flex. LEDStrip, 24V, Innen, DTW

Article nr.: 79141

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 100 mm or 12 LEDs · number of LEDs: 600 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · lumen per meter: 772 lm · Light colour: 3300 K - 1900 K (Dim To Warm) · voltage: 24 V DC · power per meter: 7.5 W · lifetime L70B50: >= 50.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 10 x 1,5 · dimming: < 1000 Hz · · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094791418 |
| Housing colour | Weiss |
| Length | 5000.00 mm |
| Width | 10.00 mm |
| Height | 1.50 mm |
| LED colour | 3300-1900K Dim to Warm |
| Lightoutput per fixture | 3860.00 lm |
| Lightoutput per LED | 6.43 lm |
| Lamp | including LED |

**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# VARDAflex Plus DTW 5 M- R. Flex. LEDStrip, 24V, Innen, DTW

Article nr.: 79141

## TECHNICAL DATA

| | |
|---|---|
| IP rating | 20 |
| Power | 37,5 W |
| Psb | 0,00 W |
| Current mA | 1563 mA |
| Voltage | 24 V |
| Amount of LED | 600 |
| Temperature range | -20 - 45 |
| LED per meter | 120 |
| Dimension of segments | 100.00 mm |
| Energy ffficiency class | EEK-Label_F |
| CRI | ≥ 80 |
| Lifetime L70B50 | 50.000 h |
| Lifetime L90B10 | 39.000 h |
| Suitable light source | |



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# VARDAflex Plus DTW 5 M- R. Flex. LEDStrip, 24V, Innen, DTW

Article nr.: 79141

## TECHNICAL DRAWING

