




VARDAflex 4inONE-72 - 5M-Ro. Flex.


LED Leiste, Innen, RGBBZ 2400K

Article nr.: 79551

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 83.33 mm or 6 LEDs · Number of LEDs: 360 · LED pitch: 13.89 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 935 lm · luminous flux 2400K per meter: 486 lm · Voltage: 24 V DC · Power per meter: 19,2 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 5.000 x 12 x 2.2 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel · · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795515
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 2400K
Lightoutput per fixture	4675.00 lm
Lightoutput per LED	12.99 lm
Lamp	including LED





 Secondlife-Shop

VARDAflex 4inONE-72 - 5M-Ro. Flex.

LED Leiste, Innen, RGBBZ 2400K

Article nr.: 79551

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	360
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	





 Secondlife-Shop

VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBBZ 2400K
Article nr.: 79551

TECHNICAL DRAWING

