




VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79553

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 83.33 mm or 6 LEDs · Number of LEDs: 360 · LED pitch: 13.89 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1000 lm · luminous flux 3000K per meter: 548 lm · Voltage: 24 V DC · Power per meter: 19,2 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 12 x 2.2 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795539
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 3000K
Lightoutput per fixture	5000.00 lm
Lightoutput per LED	13.89 lm
Lamp	Inklusive LED






VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBWW 3000K
Article nr.: 79553

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4.000 mA
Voltage	24 V
Amount of LED	360
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h





VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBWW 3000K
Article nr.: 79553

TECHNICAL DRAWING

