




VARDAflex 4inONE-84 - 5M-Ro. Flex. LED Leiste, Innen, RGBUWW 2700K

Article nr.: 79562

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 7.1 cm or 6 LEDs · Number of LEDs: 420 · LED pitch: 11.91 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1186 lm · luminous flux 2700K per meter: 626 lm · Voltage: 24V DC · Power per meter: 27 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 5.000 x 12 x 2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795621
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGBW 2700K
Lightoutput per fixture	5930.00 lm
Lightoutput per LED	14.12 lm
Lamp	Inklusive LED






VARDAflex 4inONE-84 - 5M-Ro. Flex.
LED Leiste, Innen, RGBUWW 2700K
Article nr.: 79562

TECHNICAL DATA

IP rating	20
Power	135 W
Current mA	5.600 mA
Amount of LED	420
Input voltage	24
Temperature range	-20 - 45
LED per meter	84
Dimension of segments	71.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h





VARDAflex 4inONE-84 - 5M-Ro. Flex.
LED Leiste, Innen, RGBUWW 2700K
Article nr.: 79562

TECHNICAL DRAWING

