




VARDaflex 4inONE-60 Reach15 - 15 M.- Rolle Flex. LED-Strip, 48V, 8W/m, IP20, RGBW 3000K

Article nr.: 79403

flexible LED Strip with self adhesive backside · for indoor use, IP20 · · can be separated every 250 mm or 15 LEDs · number of LEDs: 900 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 665 lm · luminous flux per meter 3000K: 265 lm · voltage: 48 V DC · power per meter: 8 W · lifespan L70B50: >= 36,000 h · energy efficiency class: D · LxWxH in mm: 15,000 x 12 x 2.2 · · maximum length per connection: 15 metre. New connectors for greater length. · Delivery contents: 15 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094794037
Length	15000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 3000K
Lightoutput per fixture	9975.00 lm
Lightoutput per LED	11.08 lm
Lamp	including LED
IP rating	20






**VARDAflex 4inONE-60 Reach15 - 15 M.-
Rolle Flex. LED-Strip, 48V, 8W/m, IP20,
RGBW 3000K**

Article nr.: 79403

TECHNICAL DATA

Power	120 W
Psb	0,00 W
Current mA	2500 mA
Voltage	48 V
Amount of LED	900
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	250.00 mm
Energy efficiency class	EEK-Label_D
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





**VARDAflex 4inONE-60 Reach15 - 15 M.-
Rolle Flex. LED-Strip, 48V, 8W/m, IP20,
RGBW 3000K**

Article nr.: 79403

TECHNICAL DRAWING

