



VARDAflex 48 IC Plus Profi Select - 20


**Meter Rolle Flex.LED-Strip, 48V, 14, 4W,
IP20, TW 2700-6500K, CRI90**

Article nr.: 79430

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be separated every 166.67 mm or 28 LEDs · number of LEDs: 3360 · LED pitch: 11.9 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 1579 lm · voltage: 48V DC · power per meter: 14.4 W · lifespan L70B50: >= 78,000 h · energy efficiency class: E · LxWxH in mm: 20,000 x 10 x 1.2 · · Maximum length per connection: 20 metres. New Connectors for greater length. · Delivery contents: 20 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094794303
Housing colour	Weiss
Length	20000.00 mm
Width	10.00 mm
Height	1.20 mm
LED colour	2700-6500K tunable white
Lightoutput per fixture	31580.00 lm
Lightoutput per LED	9.39 lm
Lamp	including LED





VARDAflex 48 IC Plus Profi Select - 20

**Meter Rolle Flex.LED-Strip, 48V, 14, 4W,
IP20, TW 2700-6500K, CRI90**

Article nr.: 79430

TECHNICAL DATA

IP rating	20
Power	288 W
Psb	0,00 W
Current mA	6000 mA
Voltage	48 V
Amount of LED	3360
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	168
Dimension of segments	166.67 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	78.000 h
Lifetime L90B10	36.000 h
Suitable light source	





VARDAflex 48 IC Plus Profi Select - 20

Meter Rolle Flex.LED-Strip, 48V, 14, 4W,
IP20, TW 2700-6500K, CRI90

Article nr.: 79430

TECHNICAL DRAWING

