



200mA, 927, 50mm LED-Modul, 36°, klar, 7W, IP20

Article nr.: 88867

LED module 7W with reflector · for recessed ceiling spotlights MR16 · dimmable · input current: 200 mA · power: 7W · luminous flux: 910 lm · CRI: >90 · lifetime L70B50: >= 100,000 h · beam angle: 36° · protection class III · energy efficiency class: D · Very good heat dissipation thanks to optimised aluminium heat sink · Aluminium reflector with halogen optics and uniform light distribution

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094888675
Housing colour	Silber
Height	34.00 mm
Outer diameter	50 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	910.00 lm
Lamp	including LED
IP rating	20
Power	7 W






**200mA, 927, 50mm LED-Modul, 36°,
klar, 7W, IP20**

Article nr.: 88867

TECHNICAL DATA

Psb	0,00 W
Current mA	200 mA
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
Energy efficiency class	EEK-Label_D
CRI	≥ 90
Lifetime L70B50	100.000 h
Lifetime L90B10	57.000 h
Suitable light source	





**200mA, 927, 50mm LED-Modul, 36°,
klar, 7W, IP20**
Article nr.: 88867

TECHNICAL DRAWING

