rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Tara - steckbar 12V Starre LED Leiste, IP40, 3000K 5W

Article nr.: 88071

Rigid, magnetic LED Strip for indoor use, IP40 · ideal for use as a kitchen recessed luminaire · plug & play enabled by connectors · · number of LEDs: 84 · LED pitch: 5.95 mm · beam angle: 90° · CRI: >80 · luminous flux: 530 lm · input voltage: 12V DC · power: 5 W · lifespan L70B50: >= 67.000 h · energy efficency class: F · LxWxH in mm: 512 x 12.6 x 10 · · Easy installation with solderless connector. · Maximum length per connection: 2 meter. New connectors for greater length. · Delivery contents: 1x VARDAflex Tara rigid bar, 2x mounting clip, 2x screw, · 1x end cap, 1x power connector with DC socket, 1x power connector with open wire

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094880716
Length	512.00 mm
Width	12.60 mm
Height	10.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	530.00 lm
Lightoutput per LED	6.31 lm
Lamp	Inklusive LED
IP rating	40

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Tara - steckbar 12V Starre LED Leiste, IP40, 3000K 5W

Article nr.: 88071

TECHNICAL DATA

Power	5 W
Current mA	417 mA
Voltage	12 V
Amount of LED	84
Material	Aluminium
Temperature range	-20 - 45
LED per meter	168
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	67.000 h