rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

# Vardaflex Wallpaper Select IP54 LD Flex.LEDSheet, 24V 6000-2700K CRI95

Article nr.: 36229

with self-adhesive backside, · for indoor and outdoor use, IP54 · · can be seperated every 26.67 x 26.67 mm or 2 LEDs · number of LEDs: 324 · LED pitch: 26.67 mm · min. bending diameter: 30 mm · beam angle: 120° · CRI: >90 · luminous flux: 4.662 lm · voltage: 24V DC · power: 72 W · power per LED: 0.22 W · lifetime L70: >= 50.000 h · LxWxH in mm: 480 x 240 x 3 · · Maximum amount per connection: 4 x VARDAflex Wallpaper · Delivery contents: 1x flexible circuit board

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094362298 |
| Length | 480.00 mm |
| Width | 240.00 mm |
| Height | 3.00 mm |
| Lightoutput per fixture | 4662.00 lm |
| Lightoutput per LED | 14.39 lm |
| Lamp | including LED |
| IP rating | 54 |
| Power | 72 W |

**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

# Vardaflex Wallpaper Select IP54 LD Flex.LEDSheet, 24V 6000-2700K CRI95

Article nr.: 36229

## TECHNICAL DATA

| | |
|---|---|
| Current mA | 3000 mA |
| Voltage | 24 V |
| Amount of LED | 324 |
| Temperature range | -20 - 45 |
| Dimension of segments | 26.67 mm |
| CRI | ≥ 90 |
| Suitable light source | |