rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



weiss 4000K NINQITA LED DL 15W IP40 53° 400mA

Article nr.: 41151

for indoor use, IP40 · · Housing: diecast aluminum (plastic protection cover, transparent) · housing colour: white · not swivelling · beam angle: 53° · power: 15 W · light colour: 4000 K (100K) neutral white · luminous flux: 1610 lm · CRI: >80 · lifespan L70: >= 50.000 h · input: 400 mA DC · protection class III · · installation depth: 95 mm · ceiling cut-out: 125 mm · outer diameter: 134 mm · energy efficiency class: A+ · not including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094411514
Housing colour	Weiss
Height	85.00 mm
Outer diameter	134 mm
Hole size	125 mm
Depth in ceiling	95.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	1610.00 lm
Lightoutput per LED	1610.00 lm



rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



weiss 4000K NINQITA LED DL 15W IP40 53° 400mA

Article nr.: 41151

TECHNICAL DATA

Lamp	including LED
IP rating	40
Power	15 W
Current mA	400 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 80
Suitable light source	

