




## sand Silber, 3000K CALA - 14W IP43 36° 350mA

Article nr.: 42149

· Housing: diecast aluminum (glass protection, transparent) · Housing colour: sand Silber · not swivelling · Beam angle: 36° · Power: 14 W · Light colour: 3000 K · Light flux: 1450 lm · CRI: >80 · Lifespan L70B50: >= 50.000 h · Input current: 350 mA DC · protection class III · Installation depth: 110 mm · Ceiling cut-out: 105 mm · Outer diameter: 116 mm · Energie efficiency class: E · not including LED converter · SECONDLIFE ITEM -heavily discounted- only while stocks last!

### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | pcs                |
| BAR code                | 4012094421490      |
| Housing colour          | Sand Silber        |
| Height                  | 80.00 mm           |
| Outer diameter          | 116 mm             |
| Hole size               | 105 mm             |
| Depth in ceiling        | 110.00 mm          |
| LED colour              | ca. 3000K warmweiß |
| Lightoutput per fixture | 1450.00 lm         |
| Lamp                    | including LED      |





## sandsilber, 3000K CALA - 14W IP43 36° 350mA

Article nr.: 42149

### TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 43          |
| Power                   | 14 W        |
| Current mA              | 350 mA      |
| Lamp base               | ohne        |
| Amount of LED           | 1           |
| Material                | Aluminium   |
| Temperature range       | -20 - 40    |
| Energy efficiency class | EEK-Label_E |
| CRI                     | ≥ 80        |
| Lifetime L70B50         | 50.000 h    |
| Suitable light source   |             |





**sandsilber, 3000K CALA - 14W IP43 36°  
350mA**

Article nr.: 42149

## TECHNICAL DRAWING



Ø 105 mm

