



**TALAN M DA210mm, Rund-Panel, Multi-
W+Lf, Plug&play starr, rund, 9/14/18W,
27/30/4000K, CRI80-weiss, IP44**

Article nr.: 48502

for indoor use, IP44 · with switchable light colour and power on the converter · housing: diecast aluminium, PMMA cover matt · housing colour: white · not swiveling · beam angle: 110° · power: 9/14/18 W · light colour: 2700/3000/4000 K · luminous flux: 1025/1500/1930 lm · CRI: >80 · lifespan L70B50: >= 45,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 30 mm · ceiling cut out: 210 mm · outer diameter: 220 mm · including constant current converter · with connector for plug-and-play-operation with 380 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 113.5 x 35.5 x 23.5 · this product contains a light source of energy efficiency class E · _Driver MOQ 1000 pcs - please add details about quantity to order with reference TALAN DRIVER 485X

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094485027
Housing colour	Weiss
Height	18.00 mm
Outer diameter	220 mm
Hole size	210 mm
Depth in ceiling	30.00 mm
LED colour	2700/3000/4000 K umschaltbar
Lightoutput per fixture	1930.00 lm
Lamp	including LED





TALAN M DA210mm, Rund-Panel, Multi-W+Lf, Plug&play starr, rund, 9/14/18W, 27/30/4000K, CRI80-weiss, IP44

Article nr.: 48502

TECHNICAL DATA

IP rating	44
Power	9-18 W
Voltage	220-240 V
Material	Aluminium
Temperature range	-10 - 40
CRI	≥ 80
Lifetime L70B50	45.000 h
Lifetime L90B10	36.000 h
Suitable light source	





**TALAN M DA210mm, Rund-Panel, Multi-
W+Lf, Plug&play starr, rund, 9/14/18W,
27/30/4000K, CRI80-weiss, IP44**

Article nr.: 48502

TECHNICAL DRAWING

