rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Pro 2, 5 M- R. LD Flex.LEDStrip, 24V, Innen, 3000K CRI90

Article nr.: 71327

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be seperated every 31.25 mm or 8 LEDs · number of LEDs: 640 · LED pitch: 3,91 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 3825 lm · voltage: 24 V DC · power per meter: 34 W · lifespan L70B50: >= 36,000 h · energy efficiency class: E · LxWxH in mm: 2.500 x 12 x 1.4 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 2.5 meter. New connectors for greater length. · Delivery contents: 2.5 meter roll with 120 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094713274
Length	2500.00 mm
Width	12.00 mm
Height	1.40 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	9563.00 lm
Lightoutput per LED	14.94 lm
Lamp	including LED
IP rating	20

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Pro 2, 5 M- R. LD Flex.LEDStrip, 24V, Innen, 3000K CRI90

Article nr.: 71327

TECHNICAL DATA

Power	85 W
Psb	0,00 W
Current mA	3541 mA
Voltage	24 V
Amount of LED	640
Temperature range	-25 - 40
LED per meter	256
Dimension of segments	31.25 mm
Energy ffficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	36.000 h
Suitable light source	

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Pro 2, 5 M- R. LD
Flex.LEDStrip, 24V, Innen, 3000K CRI90

Article nr.: 71327

TECHNICAL DRAWING

