rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex 5inONE-96 5M-R.2400K-6500K Flex.LED-Strip, 24V, Innen, RGB/BZ/W

Article nr.: 74518

flexible LED Strip with self adhesive backside, · for indoor use. · · Can be seperated every 6.25 cm or 6 LEDs · Number of LEDs: 480 · LED pitch: 10.42 mm · beam angle: 120° · CRI: >80 · Lumen per meter: 1681 lm · Voltage: 24V DC · Power per meter: 25 W · Lifetime L70: >= 36.000h · energy efficiency class: F · LxWxH in mm: 5.000 x 12 x 2.3 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094745183
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.30 mm
LED colour	RGBWWW 6500-2400K
Lightoutput per fixture	8405.00 lm
Lightoutput per LED	17.51 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex 5inONE-96 5M-R.2400K-6500K Flex.LED-Strip, 24V, Innen, RGB/BZ/W

Article nr.: 74518

TECHNICAL DATA

IP rating	20
Power	125 W
Current mA	5208 mA
Voltage	24 V
Amount of LED	480
Temperature range	-20 - 45
LED per meter	96
Dimension of segments	62.50 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Suitable light source	