rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin TVQ RGB-3000K LD Flex.LEDStrip, 24V, RGBW 5M 75W

Article nr.: 76076

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP68 · · Cuttable every 83.33 mm / 7 LEDs · Amount of LEDs: 420 · LED pitch: 11.91 mm · Beam angle: 160° · CRI: >80 · Light flux per meter: 450 lm · Voltage: 24V DC · Power per Meter: 15 W · Lifetime L70: >= 36.000 h · LxWxH in mm: 5.000 x 16 x 17 · · Temperature range: -40 to +50°C · Processing temperature: +10 to +45°C · Maximum length per connection: 8 meter · Bending radius: 150 mm · · Easy Connection with solderless connector. · Delivery contents: 5 meter roll, already with a feed connector, · 300 mm cable and end cap · Attention: do not run all colours at same time under maximum load (max. 80%)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094760766
Housing colour	Weiss
Length	5000.00 mm
Width	16.00 mm
Height	17.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	2250.00 lm
Lightoutput per LED	5.35 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin TVQ RGB-3000K LD Flex.LEDStrip, 24V, RGBW 5M 75W

Article nr.: 76076

TECHNICAL DATA

IP rating	68
Power	75 W
Psb	0,00 W
Current mA	3125 mA
Voltage	24 V
Amount of LED	420
Temperature range	-40 - 50
LED per meter	84
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin TVQ RGB-3000K LD Flex.LEDStrip, 24V, RGBW 5M 75W

Article nr.: 76076

TECHNICAL DRAWING

