rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Superior Plus Profi 5 M- R.

LD Flex.LEDStrip, 24V, Innen, 3000K CRI98

Article nr.: 79135

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be seperated every 33.33 mm or 6 LEDs · number of LEDs: 900 · LED pitch: 5.55 mm · beam angle: 120° · CRI: 98 · luminous flux per meter: 1200 lm · voltage: 24V DC · power per meter: 14.4 W · lifetime L70B50: >= 50,000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 8 x 1.4 · · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094791357
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	1.40 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	6000.00 lm
Lightoutput per LED	6.66 lm
Lamp	including LED



rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Superior Plus Profi 5 M- R.

LD Flex.LEDStrip, 24V, Innen, 3000K CRI98

Article nr.: 79135

TECHNICAL DATA

IP rating	20
Power	72 W
Psb	0,00 W
Current mA	3000 mA
Voltage	24 V
Amount of LED	900
Temperature range	-20 - 45
LED per meter	180
Dimension of segments	33.33 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 98
Lifetime L70B50	50.000 h
Suitable light source	



rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Superior Plus Profi 5 M- R.

LD Flex.LEDStrip, 24V, Innen, 3000K CRI98

Article nr.: 79135

TECHNICAL DRAWING

