



VARDAflex Superior REACH25 M- R.


**WW LD Flex.LEDStrip, 24V, Innen,
3000K CRI98**

Article nr.: 79315

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 1500 · LED pitch: 16,67 mm · beam angle: 120° · CRI: 98 · IC module on board (constant current module) · Lumen per meter: 354 lm · Voltage: 24V DC · Power per meter: 4,8 W · Lifetime L70: >= 50.000h · energy efficiency class: G · LxWxH in mm: 25.000 x 10 x 1,6 · Easy installation with solderless connector (optional). · Maximum length per connection: 25 meter. New connectors for greater length. · Delivery contents: 25 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094793153
Housing colour	Weiss
Length	25000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	8850.00 lm
Lightoutput per LED	5.90 lm
Lamp	including LED





VARDaflex Superior REACH25 M- R.

WW LD Flex.LEDStrip, 24V, Innen,
3000K CRI98

Article nr.: 79315

TECHNICAL DATA

IP rating	20
Power	120 W
Psb	0,00 W
Current mA	5000 mA
Voltage	24 V
Amount of LED	1500
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 98
Lifetime L70B50	36.000 h
Suitable light source	

