rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

VARDAflex 4inONE-60 - 5M-Ro. LD Flex. LED Leiste, Innen, RGBW 6500K

Article nr.: 79545

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be seperated every 100 mm or 6 LEDs · Number of LEDs: 300 · LED pitch: 16,67 mm · beam angle: 120° · CRI: >80 · Lumen per meter: 1084 lm (white: 545 lm) · Voltage: 24V DC · Power per meter: 19.2 W · Lifetime L70: >= 50.000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 12 x 2 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795454
Housing colour	ohne
Length	5000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGBW 6500K
Lightoutput per fixture	5420.00 lm
Lightoutput per LED	18.07 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

VARDAflex 4inONE-60 - 5M-Ro. LD Flex. LED Leiste, Innen, RGBW 6500K

Article nr.: 79545

TECHNICAL DATA

IP rating	20
Power	96 W
Psb	0,00 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	300
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy ffficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	