




VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79553

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 83.33 mm or 6 LEDs · Number of LEDs: 360 · LED pitch: 13.89 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1229 lm (white: 605 lm) · Voltage: 24 V DC · Power per meter: 19,2 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 12 x 2.2 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795539
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 3000K
Lightoutput per fixture	6145.00 lm
Lightoutput per LED	17.07 lm
Lamp	including LED





VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K Article nr.: 79553

TECHNICAL DATA

IP rating	20
Power	96 W
Psb	0,00 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	360
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	





VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBWW 3000K
Article nr.: 79553

TECHNICAL DRAWING

