rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Para Supra Eco CRI95 - 3M-R. 24V, 47W/m, 940+, 3m

Article nr.: 79858

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 3.56 cm or 8 LEDs · number of LEDs: 672 · LED pitch: 8.91 mm · beam angle: 120° · CRI: >95 · IC module on board (constant current module) · lumen per meter: 5095 lm · voltage: 24V DC · power per meter: 47 W · lifetime L70: >= 50.000 h · energy efficiency class: A+ · LxWxH in mm: 3.000 x 12 x 1.8 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 3 meter. New connectors for greater length. · Delivery contents: 3 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094798585
Housing colour	Weiss
Length	3000.00 mm
Width	12.00 mm
Height	1.80 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	15285.00 lm
Lightoutput per LED	22.74 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Para Supra Eco CRI95 - 3M-R. 24V, 47W/m, 940+, 3m

Article nr.: 79858

TECHNICAL DATA

IP rating	20
Power	141 W
Current mA	5875 mA
Amount of LED	672
Input voltage	24
Temperature range	-20 - 45
LED per meter	224
Dimension of segments	35.64 mm
CRI	≥ 95
Suitable light source	