




VARDAflex Eco Standard Reach30 M-R. LD Flex.LEDStrip, 24V, Innen, 2700K

Article nr.: 82317

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 1800 · LED pitch: 16,67 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · Lumen per meter: 237 lm · Voltage: 24V DC · Power per meter: 3 W · Lifetime L70B50: >= 36,000 h · energy efficiency class: G · LxWxH in mm: 30,000 x 10 x 1.5 · Easy installation with solderless connector (optional). · Maximum length per connection: 30 meter. New connectors for greater length. · Delivery contents: 30 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094823171
Housing colour	Weiss
Length	30000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	7110.00 lm
Lightoutput per LED	3.95 lm
Lamp	including LED






VARDAflex Eco Standard Reach30 M-R.
LD Flex.LEDStrip, 24V, Innen, 2700K
 Article nr.: 82317

TECHNICAL DATA

IP rating	20
Power	90 W
Current mA	3750 mA
Voltage	24 V
Amount of LED	1800
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Eco Standard Reach30 M-R.
LD Flex.LEDStrip, 24V, Innen, 2700K
Article nr.: 82317

TECHNICAL DRAWING

