rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

LED-Strip VARDAflex 90 Double, IP20 24V, 19, 2W/m, 940, 5m

Article nr.: 82458

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 50 mm or 8 LEDs · number of LEDs: 800 · LED pitch: 6.25 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 2181 lm · voltage: 24 V DC · power per meter: 19.2 W · lifespan L70B50: >= 50,000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 10 x 1.2 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094824581
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.20 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	10905.00 lm
Lightoutput per LED	13.63 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

LED-Strip VARDAflex 90 Double, IP20 24V, 19, 2W/m, 940, 5m

Article nr.: 82458

TECHNICAL DATA

IP rating	20
Power	96 W
Psb	0,00 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	800
Temperature range	-20 - 45
LED per meter	160
Dimension of segments	50.00 mm
Energy ffficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	28.000 h
Suitable light source	

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

LED-Strip VARDAflex 90 Double, IP20 24V, 19, 2W/m, 940, 5m

Article nr.: 82458

TECHNICAL DRAWING