




VARDAflex 5inONE-60 5M-R.2400K- 6500K Flex.LEDLeiste, 24V, Innen, RGB/BZ/W

Article nr.: 82518

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 300 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1502 lm · luminous flux 2400K+6500K per meter: 410 lm · Voltage: 24V DC · Power per meter: 24 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 5.000 x 14 x 2.5 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094825182
Housing colour	Weiss
Length	5000.00 mm
Width	14.00 mm
Height	2.50 mm
LED colour	RGBWWW 6500-2400K
Lightoutput per fixture	7510.00 lm
Lightoutput per LED	25.04 lm
Lamp	including LED






VARDAflex 5inONE-60 5M-R.2400K-6500K Flex.LEDLeiste, 24V, Innen, RGB/BZ/W

Article nr.: 82518

TECHNICAL DATA

IP rating	20
Power	120 W
Current mA	5000 mA
Amount of LED	300
Input voltage	24
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	30.000 h
Suitable light source	





**VARDAflex 5inONE-60 5M-R.2400K-
6500K Flex.LEDLeiste, 24V, Innen,
RGB/BZ/W**
Article nr.: 82518

TECHNICAL DRAWING

