




## VARDAflex Nova Plus NW 12W/M - 5MR. Flex.LEDStrip, 24V, Innen, 4000K CRI90

Article nr.: 82868

flexible LED Strip with self adhesive backside, · for indoor use. · can be separated every 5 cm or 6 LEDs · number of LEDs: 600 · LED pitch: 8,33 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · lumen per meter: 888 lm · voltage: 24V DC · power per meter: 12 W · lifetime L70: >= 36.000h · LxWxH in mm: 5.000 x 10 x 2 · Easy installation with solderless connector (optional). · Maximum length per connection: 10 meter. New connectors for greater length. · Delivery contents: 5 meter roll · · SECONDLIFE ITEM -heavily discounted- only while stocks last!

### TECHNICAL DATA

|                         |                       |
|-------------------------|-----------------------|
| Unit Code               | pcs                   |
| BAR code                | 4012094828688         |
| Housing colour          | Weiss                 |
| Length                  | 5000.00 mm            |
| Width                   | 10.00 mm              |
| Height                  | 2.00 mm               |
| LED colour              | ca. 4000K neutralweiß |
| Lightoutput per fixture | 4440.00 lm            |
| Lightoutput per LED     | 7.40 lm               |
| Lamp                    | including LED         |






## VARDAflex Nova Plus NW 12W/M - 5MR. Flex.LEDStrip, 24V, Innen, 4000K CRI90

Article nr.: 82868

### TECHNICAL DATA

|                       |          |
|-----------------------|----------|
| IP rating             | 20       |
| Power                 | 60 W     |
| Current mA            | 2500 mA  |
| Voltage               | 24 V     |
| Amount of LED         | 600      |
| Temperature range     | -20 - 45 |
| LED per meter         | 120      |
| Dimension of segments | 50.00 mm |
| CRI                   | ≥ 90     |
| Lifetime L70B50       | 36.000 h |
| Suitable light source |          |





**VARDAflex Nova Plus NW 12W/M -  
5MR. Flex.LEDStrip, 24V, Innen, 4000K  
CRI90**

Article nr.: 82868

## TECHNICAL DRAWING

