




## VARDAflex Neon Mikro TOP - 2700K LD Flex.LEDStrip, 24V, UWW ST-6M 75W

Article nr.: 83633

Flexible LED strip sealed in · UV, chlorine, salt water and · solvent-resistant white PVC · for indoor and outdoor use · single-colour · 12.5 Watt, 128 LED 475 Lumen per meter · Maximum length per connection 6 meters · bending radius 6.5cm · length of wire 30cm · temperature range -20°C up to +45°C · processing temperature +10°C up to +45°C · IP68 underwater 1m · width 10mm · height 10mm · Beam angle: 120° · 24V DC · Lifespan L70: >= 35,000 hours

### TECHNICAL DATA

|                         |                          |
|-------------------------|--------------------------|
| Unit Code               | pcs                      |
| BAR code                | 4012094836331            |
| Housing colour          | Weiss                    |
| Length                  | 6000.00 mm               |
| Width                   | 10.00 mm                 |
| Height                  | 10.00 mm                 |
| LED colour              | ca. 2700K ultra warmweiß |
| Lightoutput per fixture | 2850.00 lm               |
| Lightoutput per LED     | 2.61 lm                  |
| Lamp                    | including LED            |






**VARDAflex Neon Mikro TOP - 2700K LD**  
**Flex.LEDStrip, 24V, UWW ST-6M 75W**  
Article nr.: 83633

## TECHNICAL DATA

|                       |            |
|-----------------------|------------|
| IP rating             | 66         |
| Power                 | 75 W       |
| Current mA            | 3125 mA    |
| Voltage               | 24 V       |
| Amount of LED         | 1092       |
| Material              | Kunststoff |
| Temperature range     | -20 - 45   |
| LED per meter         | 182        |
| Dimension of segments | 38.50 mm   |
| CRI                   | ≥ 80       |
| Suitable light source |            |





**VARDAflex Neon Mikro TOP - 2700K LD**  
**Flex.LEDStrip, 24V, UWW ST-6M 75W**  
Article nr.: 83633

## TECHNICAL DRAWING

