rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex COB R-to-R Plus - 5 Meter Rolle Flex.LEDStrip, 24V, 10, 5W/m, Innen, 3000K

Article nr.: 84335

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be seperated every 50 mm or 24 LEDs · number of LEDs: 2400 · LED pitch: 2.08 mm · beam angle: 180° · CRI: >90 · luminous flux per metre: 1015 lm · voltage: 24 V DC · power per metre: 10,5 W · lifespan L70B50: >= 54,000 h · Energy efficiency class: F · LxWxH in mm: 5,000 x 8 x 2.2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094843353
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.20 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	5075.00 lm
Lightoutput per LED	2.11 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex COB R-to-R Plus - 5 Meter Rolle Flex.LEDStrip, 24V, 10, 5W/m, Innen, 3000K

Article nr.: 84335

TECHNICAL DATA

IP rating	20
Power	52,5 W
Psb	0,00 W
Current mA	2187 mA
Voltage	24 V
Amount of LED	2400
Temperature range	-20 - 40
LED per meter	480
Dimension of segments	50.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	54.000 h
Lifetime L90B10	20.000 h
Suitable light source	



rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex COB R-to-R Plus - 5 Meter Rolle Flex.LEDStrip, 24V, 10, 5W/m, Innen, 3000K

Article nr.: 84335

TECHNICAL DRAWING

