



90-264V 47/63Hz LD Konverter 250mA 6-42V 1, 5-10, 5W

Article nr.: 85002

rutecl LED converter, constant current · For indoor use, IP20 · with screw connection and strain relief · CE, REACH, RoHS, MM, SELV · Protection against short circuit and over voltage · Cable cross-section screw terminals: 0.5 - 1.5 sq mm · Housing: plastic · Input voltage: 100-240 V AC · Power: 1.5 - 10.5 W · Output current: 250 mA · LxWxH in mm: 86 x 45 x 26 · Temperature range: -20 to +40°C · Not dimmable on primary side

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835850025
Housing colour	Blau
Length	86.00 mm
Width	45.00 mm
Height	26.00 mm
Lamp	without
IP rating	20
Power	1,5-10,5 W
Pno	





90-264V 47/63Hz LD Konverter 250mA
6-42V 1, 5-10, 5W
 Article nr.: 85002

TECHNICAL DATA

Current mA	250 mA
Input voltage	100-240
Output voltage	6-42
Material	Kunststoff
Tolerance	5.00
Temperature range	-20 - 40
Suitable light source	LED





90-264V 47/63Hz LD Konverter 250mA
6-42V 1, 5-10, 5W
Article nr.: 85002

TECHNICAL DRAWING

