rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

VARDAflex Outdoor IP67 WT 10M Flex.LED Strip, 24V, IP67, 3000K 60W

Article nr.: 86705

Flexible LED Stripe sealed in UV-, chlorine-, · salt water- and solvent resistant white/transparent PVC · for indoor- and outdoor use, IP67 · · Cuttable every 166.67 mm / 6 LEDs · Amount of LEDs: 360 · LED pitch: 27.78 mm · Beam angle: 120° · CRI: >80 · Lominous flux per meter: 479 lm · Voltage: 24V DC · Power per Meter: 6 W · Lifetime L70: >= 36.000 h · Energy efficiency class: A · LxWxH in mm: 10.000 x 15.5 x 6 · · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 15 meter · Bending diameter: 50 mm · · Easy Connection with solderless connector. · Delivery contents: 10 meter roll, already with a feed connector · and end cap

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094867052
Housing colour	Weiss
Length	10000.00 mm
Width	15.50 mm
Height	6.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4790.00 lm
Lightoutput per LED	13.31 lm
Lamp	including LED

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE

VARDAflex Outdoor IP67 WT 10M Flex.LED Strip, 24V, IP67, 3000K 60W

Article nr.: 86705

TECHNICAL DATA

IP rating	67
Power	60 W
Current mA	2500 mA
Voltage	24 V
Amount of LED	360
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	36
Dimension of segments	166.67 mm
CRI	≥ 80
Suitable light source	