




VARDAflex Outdoor RGBW-3000K Int. Eight LD Flex.LED Strip, 24V, IP67, RGBW 5 M

Article nr.: 86759

Flexible LED Stripe sealed in UV-, Chlorine-, · salt water- and solvent resitant transparent PVC · for indoor- and outdoor use, IP67 · · cuttable every 125 mm / 7 LEDs · Amount of LEDs: 280 · IC type: UCS2904 · LED spacing: 17.85 mm · Beam Angle: 120° · CRI: 70 · Light flux per metre: 585 lm · Load per Meter: 15 W · Lifespan L70: >= 36.000 h · LxWxH in mm: 5.000 x 15.5 x 6 · · Temperature range: - 20 to +40°C · Processing temperature: +10 to +40°C · Maximum length per connection: 5 metre · Easy installation due to solder-free connectors · Bending diameter: 50 mm · Scope of delivery: 5 metre roll, with in-feeder connector · provided at one end and end-cap at the other end. · Attention: do not run all at same time on · maximum load (max. 80%)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094867595
Housing colour	ohne
Length	5000.00 mm
Width	15.50 mm
Height	6.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	2925.00 lm
Lightoutput per LED	10.45 lm
Lamp	including LED





VARDAflex Outdoor RGBW-3000K Int.

Eight LD Flex.LED Strip, 24V, IP67,
RGBW 5 M

Article nr.: 86759

TECHNICAL DATA

IP rating	67
Power	75 W
Current mA	3125 mA
Voltage	24 V
Amount of LED	280
Material	Kunststoff
Temperature range	-20 - 40
LED per meter	56
Dimension of segments	125.00 mm
CRI	≥ 70
Suitable light source	

