



220-240V AC, SKII LED Konverter 200mA 5W-8, 4W 25-42V

Article nr.: 87372

LED converter, constant current · for indoor use, IP20 · with terminal connection and strain relief · CE, REACH, RoHS, SELV · Protection against short circuit · Primary cable cross-section: 0.75-1.5 sqmm · Secondary cable cross-section: 0.5-1.5 sqmm · Housing: plastic · Input voltage: 220-240 V AC · Power: 5-7.2 watts · Output current: 200 mA · LxWxH in mm: 96 x 36 x 24 · Temperature range: -30 to +50°C · Primary side not dimmable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094873725
Housing colour	Weiss
Length	96.00 mm
Width	36.00 mm
Height	24.00 mm
Lamp	without
IP rating	20
Power	5-8,4 W
Pno	<0,5 W



Equiv.
SELV





220-240V AC, SKII LED Konverter 200mA 5W-8, 4W 25-42V

Article nr.: 87372

TECHNICAL DATA

Current mA	200 mA
Input voltage	220-240
Output voltage	25-42
Material	Kunststoff
Temperature range	-30 - 50
Suitable light source	LED



Equiv.
SELV





220-240V AC, SKII LED Konverter
200mA 5W-8, 4W 25-42V
Article nr.: 87372

TECHNICAL DRAWING

