



**220-240V AC, SKII,  
dimmb.Phasenabschnitt LED Konverter  
200mA 6W-8, 4W 30-42V**  
Article nr.: 87375

LED converter, constant current-dimmable · for indoor use, IP20 · with screw connection and strain relief · CE, REACH, RoHS, SELV · Protection against short circuit, over temperature and overload · Primary cable cross-section: 0.75-1.5 sqmm · Secondary cable cross-section: 0.5-1.5 sqmm · Housing: plastic · Input voltage: 220-240 V AC · Power: 6-8.4 watts · Output current: 200 mA · LxWxH in mm: 85 x 41 x 22 · Temperature range: -20 to +50°C · Primary side dimmable with trailing edge dimmer

## TECHNICAL DATA

|                |               |
|----------------|---------------|
| Unit Code      | pcs           |
| BAR code       | 4012094873756 |
| Housing colour | Weiss         |
| Length         | 85.00 mm      |
| Width          | 41.00 mm      |
| Height         | 22.00 mm      |
| Lamp           | without       |
| IP rating      | 20            |
| Power          | 6-8,4 W       |
| Pno            | <0,5 W        |





**220-240V AC, SKII,  
dimmb.Phasenabschnitt LED Konverter  
200mA 6W-8, 4W 30-42V**  
Article nr.: 87375

## TECHNICAL DATA

|                       |            |
|-----------------------|------------|
| Current mA            | 200 mA     |
| Input voltage         | 220-240    |
| Output voltage        | 30-42      |
| Material              | Kunststoff |
| Temperature range     | -20 - 50   |
| Suitable light source | LED        |



Equiv.  
**SELV**





**220-240V AC, SKII,  
dimmb.Phasenabschnitt LED Konverter  
200mA 6W-8, 4W 30-42V**  
Article nr.: 87375

#### TECHNICAL DRAWING

