**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE




# 0-10V 200mA-1050mA SOLO-DRIVE 100W 230V

Article nr.: 89504

230V 4x60V DMX Constant Current Dimmer for Single Color Power LEDs · Input: 122-277V AC by 230V 0,5A 50Hz max. · Output: 200-1050mA, max. 60V per Output (4 Outputs), · Total Maximum 100W · Power Factor >0,94 · Hybrid Hydra Drive: 15-bit Resolution · Dimming Control: Smooth Dimming from 100-0% (Choice of Linear or Logarithmic · Dimming Curve · Interface for External Control Device: 10k Potentiometer, · 0-10V Source or Switch · High Efficiency at Higher Watts and Volts Range: 90% at full load, ? 87% at · Loads 50W · ENEC (VDE) Tested · IEC 61347-1, IEC 61347-2-13, IEC 62384+A1, EN 55015 + A1, EN55022 + A1, IEC · 61000-3-2, EN61547, IEC 62386-207 · CE · SECONDLIFE ITEM -heavily discounted- only while stocks last!

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094895048 |
| Housing colour | Weiss |
| Length | 354.00 mm |
| Width | 42.00 mm |
| Height | 30.00 mm |
| Lamp | without |
| IP rating | 20 |
| Power | 100 W |
| Current mA | 200-1050 mA |



**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE




# 0-10V 200mA-1050mA SOLO-DRIVE 100W 230V

Article nr.: 89504

## TECHNICAL DATA

| | |
|---|---|
| Input voltage | 220-240 |
| Material | Kunststoff |
| Temperature range | -40 - 50 |
| Suitable light source | |