



**Bridgelux 2700K 43° 350mA CRI80 LED
Einbaustr. 10W Eisen geb.**
Article nr.: ALU50375UWW

for indoor use, IP 20 · · housing: diecast aluminum, aluminum reflector, transparent protective glass ·
housing color: brushed iron · 30° swivelling · beam angle: 43° · power: 10 W · light color: 2700 K ·
luminous flux: 1187 lm · CRI: >80 · lifetime L70: >= 50.000 h · input: 350 mA DC · protection class III · ·
installation depth: 90 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · energie efficiency class:
A+ · including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094403755
Housing colour	Eisen-gebürstet
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	90.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	1187.00 lm
Lamp	including LED
IP rating	20





**Bridgelux 2700K 43° 350mA CRI80 LED
Einbaustr. 10W Eisen geb.**

Article nr.: ALU50375UWW

TECHNICAL DATA

Power	10 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Suitable light source	

