



**Bridgelux 13W 1050mA ww 3000K 50°
LED Einbaustr. 13W Eisengeb.**

Article nr.: ALU53485WW

Beam Angel 50° · Adjustable, Without Snap-Ring · Integrated Power LED-Array 13W Bridgelux · For Indoor Use · Light Color: 3000 K (100 K) Warm White · Beam Angle 32° or 50° · Light Output 810 Lumen · Excluding: LED Driver 1050 mA · Optimized Aluminum Reflector With Uniform Light Distribution, · 61% Less Energy Compared to OSRAM Decostar 51 IRC 35W · Ceiling Cut-Out Only 70 mm · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094534855
Housing colour	Eisen-gebürstet
Outer diameter	83 mm
Hole size	70 mm
Depth in ceiling	100.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	810.00 lm
Lamp	including LED
IP rating	20





Bridgelux 13W 1050mA ww 3000K 50°
LED Einbaustr. 13W Eisengeb.
Article nr.: ALU53485WW

TECHNICAL DATA

Power	13 W
Current mA	1050 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Suitable light source	

