rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



3000K 38° 350mA CRI80 LED Einbaustr. 6, 2W Gold m.Konverter

Article nr.: ALU56373WW

for indoor use, IP 20 · · housing: diecast aluminum, aluminum reflector, transparent protective glass · housing color: gold · 30° swivelling · beam angle: 38° · power: 6.2 W · light color: 3000 K · luminous flux: 686 lm · CRI: >80 · lifetime L70: >= 50.000 h · input: 350 mA DC · protection class III · · installation depth: 65 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · energie efficiency class: A++ · including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094263731
Housing colour	Gold
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	65.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	686.00 lm
Lamp	including LED
IP rating	20

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



3000K 38° 350mA CRI80 LED Einbaustr. 6, 2W Gold m.Konverter

Article nr.: ALU56373WW

TECHNICAL DATA

Power	6,2 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Suitable light source	

