



**2700K 38° 350mA CRI80 LED Einbaustr.
6, 2W Eisengeb. m.Konv.**
Article nr.: ALU56375UWW

for indoor use, IP 20 · · housing: diecast aluminum, aluminum reflector, transparent protective glass ·
housing color: brushed iron · 30° swivelling · beam angle: 38° · power: 6.2 W · light color: 2700 K ·
luminous flux: 670 lm · CRI: >80 · lifetime L70: >= 50.000 h · input: 350 mA DC · protection class III · ·
installation depth: 65 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · energie efficiency class:
A++ · including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094463759
Housing colour	Eisen-gebürstet
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	65.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	670.00 lm
Lamp	including LED
IP rating	20





**2700K 38° 350mA CRI80 LED Einbaustr.
6, 2W Eisengeb. m.Konv.**
Article nr.: ALU56375UWW

TECHNICAL DATA

Power	6,2 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Suitable light source	

