




GAIL LED-Einbaustrahler3er Set

**DimToWarm Plug&play schw., rund,
300mA, 3x6W, IP40, 3-1800K, CRI80-
schwarz matt**

Article nr.: ALU57332DTW

for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: black · swiveling · beam angle: 36° · power: 6 W · light colour: 3000/1900 K Dim To Warm · luminous flux: 430 lm · CRI: >95 · lifespan L70B50: >= 50,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector and 3-way distributor for plug-and-play-operation · each downlight has 2 metres connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 120 x 45 x 28 · this product contains a light source of energy efficiency class G · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094573427
Housing colour	schwarz matt
Height	40.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	3000-1900K Dim to Warm
Lightoutput per fixture	430.00 lm
Lamp	including LED



Equiv.
SELV





 Secondlife-Shop

GAIL LED-Einbaustrahler3er Set

**DimToWarm Plug&play schw., rund,
300mA, 3x6W, IP40, 3-1800K, CRI80-
schwarz matt**

Article nr.: ALU57332DTW

TECHNICAL DATA

IP rating	40
Power	6 W
Current mA	300 mA
Voltage	220-240 V
Output voltage	31-62
Material	Aluminium
Tolerance	5.00
Efficiency	86.00
Temperature range	-30 - 40
CRI	≥ 95
Lifetime L70B50	50.000 h
Suitable light source	



Equiv.
SELV

