



GLIN 3000K 24° 500mA IP40 m.Scheibe LED Einbaustr.20W Weiß o.Konv.

Article nr.: ALU58801WWOK

for indoor use, IP40 · Housing: diecast aluminum (protective glass, transparent) · Housing colour: white · swivel · Beam angle: 24° · Power: 20 W · Light colour: 3000 K (100K) warm white · Luminous flux: 1968 lm · CRI: >80 · Lifespan L70: >= 50.000 h · Input current: 500 mA DC · protection class III · Installation depth: 110 mm · Ceiling cut-out: 105 mm · Outer diameter: 116 mm · not including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094588018
Housing colour	Weiss
Height	95.00 mm
Outer diameter	116 mm
Hole size	105 mm
Depth in ceiling	110.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1968.00 lm
Lightoutput per LED	1968.00 lm





**GLIN 3000K 24° 500mA IP40 m.Scheibe
LED Einbaustr.20W Weiß o.Konv.**

Article nr.: ALU58801WWOK

TECHNICAL DATA

Lamp	including LED
IP rating	40
Power	20 W
Current mA	500 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 80
Suitable light source	

