




**GLIN 3000K 24° 500mA IP40 m.Scheibe
LED Einbaustr. 20W Weiß o.Konv. Eckig**
Article nr.: ALU58811WWOK

for indoor use, IP40 · · Housing: diecast aluminum (protective glass, transparent) · Housing colour: white · swivel · Beam angle: 24° · Power: 20 W · Light colour: 3000 K (100K) warm white · Light flux: 1968 lm · CRI: >80 · Lifespan L70: >= 50.000 h · Input current: 500 mA DC · protection class III · · Installation depth: 110 mm · Ceiling cut-out: 105 mm · Outer diameter: 116 x 116 mm · Energie efficiency class: A+ · not including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094588117
Housing colour	Weiss
Length	116.00 mm
Width	116.00 mm
Height	95.00 mm
Hole size	105 mm
Depth in ceiling	110.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1968.00 lm





**GLIN 3000K 24° 500mA IP40 m.Scheibe
LED Einbaustr. 20W Weiß o.Konv. Eckig**
Article nr.: ALU58811WWOK

TECHNICAL DATA

Lightoutput per LED	1968.00 lm
Lamp	including LED
IP rating	40
Power	20 W
Current mA	500 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 80
Suitable light source	

