**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



# CYRA+ XL Refit LED-Downlight, DALI, Refl., fa. starr, rd, 230V, 7/9/14/18/24W, IP20, 3000K, CRI80, RAL9016, 60°

Article nr.: C+XL-1-4-WW-80-60-12

Downlight for indoor use, IP20 · Front ring of galvanised sheet steel, powder-coated · COB module carrier and lens interchangeable · Faceted trumpet reflector made of ultra-pure aluminium, highly specular · Housing colour: RAL9016 · High-quality PMMA optic for precise light control and very good glare control · Homogeneous symmetrical illumination, UGR<19 · Beam angle: 60° · Power: 7, 9, 14, 18 or 24 W · Light colour: 3000 K · Luminous flux: 1030, 1280, 2000, 2500 or 3465 lm · CRI: >80 · Lifespan L70B50: >= 60,000 h · Lifespan L80B10: >= 50,000 h · Input voltage: 220-240 V AC, 50/60 Hz · Protection class II · Installation depth: 85 mm · Ceiling cut-out: 275-300 mm · Outer diameter: 320 mm · Tool-free installation in the ceiling with tension springs that adapt to the ceiling thickness · (1 - 30 mm) · Installation in concrete pots possible · Control gear with luminaire cable pre-assembled for easy installation · Suitable for through-wiring · Dimmable via DALI-2 or Push-Dim · Can be used in central battery emergency lighting systems in accordance with EN61347-2-13 Annex J · This product contains a light source of energy efficiency class D

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094189819 |
| Housing colour | weiß RAL9016 |
| Height | 85.00 mm |
| Outer diameter | 320 mm |
| Hole size | 300 mm |
| Depth in ceiling | 85.00 mm |
| LED colour | ca. 3000K warmweiß |
| Lightoutput per fixture | 3465.00 lm |
| Lamp | including LED |



**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



# CYRA+ XL Refit LED-Downlight, DALI, Refl., fa. starr, rd, 230V, 7/9/14/18/24W, IP20, 3000K, CRI80, RAL9016, 60°

Article nr.: C+XL-1-4-WW-80-60-12

## TECHNICAL DATA

| | |
|---|---|
| IP rating | 20 |
| Power | 7-24 W |
| Psb | 0,00 W |
| Current mA | 200-700 mA |
| Voltage | 220-240 V |
| Lamp base | ohne |
| Amount of LED | 1 |
| Material | Aluminium |
| Temperature range | -20 - 50 |
| CRI | ≥ 80 |
| Lifetime L70B50 | 60.000 h |
| Lifetime L90B10 | 42.000 h |
| Suitable light source | |



**rutec LIGHTDESIGN GmbH** | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



# CYRA+ XL Refit LED-Downlight, DALI, Refl., fa. starr, rd, 230V, 7/9/14/18/24W, IP20, 3000K, CRI80, RAL9016, 60°

Article nr.: C+XL-1-4-WW-80-60-12

## TECHNICAL DRAWING

