




Light Designers Choice 126MU 5 meter Flex.LEDStrip, 24V, Innen, 3000K 5/10/19W

Article nr.: LDC1230MU

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be separated every 166.67 mm or 21 LEDs · number of LEDs: 630 · LED pitch: 7,93 mm · beam angle: 120° · CRI: >80 · luminous flux per meter at 5 W: 670 lm · luminous flux per meter at 10 W: 1170 lm · luminous flux per meter at 19 W: 2075 lm · voltage: 24V DC · power per meter: 5/10/19 W · lifespan L70B50: >= 60,000 h · energy efficiency class: E · LxWxH in mm: 5,000 x 12 x 1,3 · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835712309
Length	5000.00 mm
Width	12.00 mm
Height	1.30 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	10375.00 lm
Lightoutput per LED	16.46 lm
Lamp	including LED
IP rating	20






Light Designers Choice 126MU 5 meter Flex.LEDStrip, 24V, Innen, 3000K 5/10/19W

Article nr.: LDC1230MU

TECHNICAL DATA

Power	95 W
Psb	0,00 W
Current mA	3958 mA
Voltage	24 V
Amount of LED	630
Temperature range	-20 - 45
LED per meter	126
Dimension of segments	166.67 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	60.000 h
Suitable light source	





Light Designers Choice 126MU 5 meter
Flex.LEDStrip, 24V, Innen, 3000K
5/10/19W

Article nr.: LDC1230MU

TECHNICAL DRAWING

