



Aluminium gebürstet ohne Konverter MELIMAR - Kard.Strahler, 1fach-LED, Rund

Article nr.: LED57540WWOK

for indoor use, IP 20 · · housing: solid aluminum · housing color: brushed aluminum · swivel · beam angle: 35° · power: 6 W · light color: 3000 K · luminous flux: 568 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 600 mA DC · protection class III · · installation depth: 80 mm · ceiling cut-out: 80 mm · outer diameter: 92 mm · energie efficiency class: F · not included LED converter · SECONDLIFE ITEM - heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094575407
Housing colour	Aluminium
Height	53.00 mm
Outer diameter	92 mm
Hole size	80 mm
Depth in ceiling	80.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	568.00 lm
Lamp	including LED





Aluminium gebürstet ohne Konverter
MELIMAR - Kard.Strahler, 1fach-LED, Rund
Article nr.: LED57540WWOK

TECHNICAL DATA

IP rating	20
Power	6 W
Current mA	600 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	

