



Aluminium gebürstet ohne Konverter QU. MELIMAR - Kard.EB-Strahler, 1fach-LED

Article nr.: LED57541WWOK

for indoor use, IP 20 · · housing: solid aluminum · housing color: brushed aluminum · swivel · beam angle: 35° · power: 6 W · light color: 3000 K · luminous flux: 568 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 600 mA DC · protection class III · · installation depth: 80 mm · ceiling cut-out: 80 mm · outer dimensions: 92 x 92 mm · energie efficiency class: F · not included LED converter · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094575414
Housing colour	Aluminium
Length	92.00 mm
Width	92.00 mm
Height	53.00 mm
Hole size	80 mm
Depth in ceiling	80.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	568.00 lm





Aluminium gebürstet ohne Konverter QU. MELIMAR - Kard.EB-Strahler, 1fach-LED

Article nr.: LED57541WWOK

TECHNICAL DATA

Lamp	including LED
IP rating	20
Power	6 W
Current mA	600 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	

