



VARDAflex Osmium FEMTO TVQ 4000K LD S?-?? Flex.LEDStrip, 24V, NW

Article nr.: S71628

flexible LED Stripe sealed in UV- and · saltwater resistant white silicone · for indoor- and outdoor use, IP65 · · cuttable every 50 mm / 7 LEDs · amount of LEDs per meter: 140 · LED pitch: 7.14 mm · beam angle: 110° · CRI: >90 · luminous flux per meter: 660 lm · power per meter: 13 W · lifetime L70B50: >= 50,000 h · WxH in mm: 11 x 11 · · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending radius vertical: 55 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094716282
Housing colour	Weiss
Width	11.00 mm
Height	11.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per LED	4.71 lm
Lamp	including LED
IP rating	65
Psb	0,00 W






VARDAflex Osmium FEMTO TVQ 4000K
LD S?-?? Flex.LEDStrip, 24V, NW
Article nr.: S71628

TECHNICAL DATA

Voltage	24 V
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
CRI	≥ 90
Lifetime L70B50	50.000 h
Suitable light source	





VARDAflex Osmium FEMTO TVQ 4000K
LD S?-?? Flex.LEDStrip, 24V, NW
Article nr.: S71628

TECHNICAL DRAWING

