



VARDAflex Osmium TVQ RGBW-3000K LD S?-?? Flex.LEDStrip, 24V, RGBW

Article nr.: S71665

flexible LED Stripe sealed in UV- and · saltwater resistant white silicone · for indoor- and outdoor use, IP65 · · cuttable every 71.4 mm / 6 LEDs · amount of LEDs per meter: 84 · LED pitch: 11.9 mm · beam angle: 110° · CRI: >80 · luminous flux per meter: 354 lm · power per meter: 15.6 W · lifetime L70B50: >= 36,000 h · WxH in mm: 16 x 16 · · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending radius vertical: 65 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094716657
Housing colour	Weiss
Width	16.00 mm
Height	16.00 mm
LED colour	RGBW 3000K
Lightoutput per LED	4.21 lm
Lamp	including LED
IP rating	65
Psb	0,00 W





VARDAflex Osmium TVQ RGBW-3000K
LD S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S71665

TECHNICAL DATA

Voltage	24 V
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	84
Dimension of segments	71.40 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	

